

## New IAC 252 Series Mini Sound Shelter

IAC began production of the new 252 Sound Shelter replacing the older style 250 sound shelter. The 252's new design is engineered to allow flexibility in any environment. The new IAC 252 Sound Shelter can be quickly transformed to achieve a right or left hand configuration. The "transformation" from "right" to "left" or "space" to "space" can be accomplished in a "New York Minute" without any disassembly of components, by any staff member, and without any tools.



The new 252 Sound Shelter is:

### Ideally Suited For:

- Industrial-Monitoring Audiometry
- Public School – Identification Audiometry
- Speech Audiometry (through earphones)
- Psychological Data Recording
- Hearing Health Professionals
- Mobile Test Vans

### Equipped With:

- Noise-Lock® magnetic-seal doors for safety
- Tranquil-Aire® silent forced ventilation system
- Outside mounted shelf – 16 in. x 32 in.
- Casters for ready positioning or repositioning of booth

### Ready To Go To Work:

- Shipped fully equipped and assembled
- Passes through any normal 30 in. (762mm) wide door
- I.D. – 24 in. wide x 34 in. deep x 66 in. high (610x864x1676mm)
- O.D. – 29 in. wide x 39 in. deep x 75 in. high (737x991x1905mm)
- Floor area is less than 8 sq.ft. (0.74sq m)
- Net weight – 650 lb. (295 kg)
- Shipping weight – 710 lb. (322 kg)

The room is available in "Khaki" color from stock for immediate shipment. For special configurations or choice of nine standard colors please give us a call at IAC America (718) 931-8000.

The new 252 Mini Sound Shelter carries the American Mark of Safety and is UL listed as an assembly.